Product code Description Presto Spachtel styrolfrei mit Härter alle Qualitäten mofakult.ch mofakult.ch mofakult.ch mofakult.ch mofakult.ch 479694alt mofakult.cComponents: Presto Spachtel styrolfrei alle Qualitäten 443367S Hardener Paste

Kit Components

22.11.2021



Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2021 Version number 9 (replaces version 8) Revision: 22.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Presto Spachtel styrolfrei alle Qualitäten
- · Article number:

443367S, 443374S, 443381S, 443466S, 443480S, 443503S, 443534S, 443541S, 443558S, 443565S, 443572S, 443589S, 443596S, 443602S, 443619S, 443633S, 443664S, 443671S, 443688S, 443718S, 443725S, 443732S, 443800S, 479663S, 479670S, 479687S, 479694Salt, 479700S akulken

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- mofal ult.ch · Product category Hardener
 - · Process category PROC10 Roller application or brushing
 - · Application of the substance / the mixture Knife filler/ Surfacer
 - · 1.3 Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

- *Formerly known as Motip Dupli GmbH
- mofal ult.ch. Further information obtainable from: Department Product Safety
 - · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergeny phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if childs have been poisened: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

(Contd. on page 2)

mofakult.ch

mofakult.ch

mofakult.ch

mofakult.ch

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2021 Version number 9 (replaces version 8) Revision: 22.04.2021

Trade name: Presto Spachtel styrolfrei alle Qualitäten

(!)

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Warning

mofal ult.ch. Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P264 Wash thoroughly after handling. P280 Wear protective gloves / eye protection.

P302+P352 FON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with regional regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous	components:
-------------	-------------

CAS: 25013-15-4 EINECS: 246-562-2 Reg.nr.: 01-2119622074-50 Vinyltoluene

🕸 Flam. Liq. 3, H226

Asp. Tox. 1, H304

Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2,

(Contd. on page 3)

10-<12.5%

- CI

mofakult.ch

(Contd. of page 1) fakult.ch

mofakult.ch

mofakult.ch

mofakult.ch

Jrheber des Dokuments bleibt der ursprüngliche Herausg

mofakult

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2021 Version number 9 (replaces version 8) Revision: 22.04.2021

Trade name: Presto Spachtel styrolfrei alle Qualitäten

	mofakult.ch	mofakult.ch		Contd. of page 2)
	27-43-7 · 231-784-4 01-2119491274-35	barium sulphate, natural substance with a Community workplace ex	posure limit	5-<10%
tch Index nu	· 204-617-8 mber: 604-005-00-4	1,4-dihydroxybenzene Muta. 2, H341; Carc. 2, H351 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Acute Tox. 4, H302; Skin Sens. 1, H317	mofakult.ch	≤0.5%

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

No further relevant information available.

- · 5.3 Advice for firefighters -
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

 $See\ Section\ 13\ for\ disposal\ information.$

mofakult.cl (Contd. on page 4)

mofakult.ch

mofakult.ch

mofakult.ch

mofakult.ch

eber des Dokuments bleibt der ursprüngliche Herausgek

Printing date 22.11.2021 *Version number 9 (replaces version 8)* Revision: 22.04.2021

Trade name: Presto Spachtel styrolfrei alle Qualitäten

(Contd. of page 3)

mofakult.ch

mofakult.ch

mofakult.ch

mofakult.ch

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special measures required.
- · Information about fire and explosion protection:

mofal ult.ch Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- \cdot 7.3 *Specific end use*(s) *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

- Ult.Ch. 8.1 Control parameters
 - · Ingredients with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust

123-31-9 1,4-dihydroxybenzene

WEL Long-term value: 0.5 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

- Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection



Protective gloves

mofal ultich. Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 5)

Printing date 22.11.2021 Version number 9 (replaces version 8) Revision: 22.04.2021

Trade name: Presto Spachtel styrolfrei alle Qualitäten

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

• Odour: Characteristic• Odour threshold: Not determined.

• Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 145 °C (293 °F)
Not applicable.

· Lower and upper explosion limit

Lower: 1.2 Vol %
Upper: 8.9 Vol %
Flash point: 33 °C (91.4 °F)
Decomposition temperature: Not determined.

• pH morakul ch Mixture is non-soluble (in water).

· Viscosity:

• Kinematic viscosity Not determined.
• Dynamic: Not determined.

· Solubility

mofakult

cult

water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C (68 °F): 6 hPa (4.5 mm Hg)

· Density and/or relative density

• Density at 20 °C (68 °F): 0.7-1.9 g/cm³ (5.8-15.9 lbs/gal)

Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health and environment, and on safety.

• Ignition temperature: 480 °C (896 °F)

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• Organic solvents: 0.3 % • VOC (EC) --- 80-205 g/l

• VOC-EU%
 • Solids content: kult.ch
 12.00 %
 88.0 % of akult.ch

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void
· Flammable gases Void
mofabult ch Aerosols Void

(Contd. on page 6)

GB

(Contd. of page 4) falult.ch

mofakult.ch

mofakult.ch

mofakult.ch

Printing date 22.11.2021 Version number 9 (replaces version 8) Revision: 22.04.2021

Trade name: Presto Spachtel styrolfrei alle Qualitäten

5	mofakult.ch	S	m	ofakult.ch	(Con	td. of page 5) Takult.ch
	· Oxidising gases		Void			
	· Gases under pressure		Void			
	· Flammable liquids		Flamma	ble liquid and vo	apour.	
	· Flammable solids		Void	_		
	· Self-reactive substances and mix	tures	Void			
mofakult	Pyrophoric liquids		Void			
	· Pyrophoric solids		Void			
	· Self-heating substances and mix	tures	Void			
	· Substances and mixtures, which	emit flammable				
	gases in contact with water	•	Void			
	· Oxidising liquids		Void			
	· Oxidising solids which		Void m			mofakult.ch
	· Organic peroxides		Void			
	· Corrosive to metals		Void			
	· Desensitised explosives		Void			

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- mofal ult.ch. 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 mofakult.ch
 - · Acute toxicity
 - · LD/LC50 values relevant for classification:

25013-15-4 Vinyltoluene

Oral	LD50	3375 mg/kg (rat)
	LD50	4585 mg/kg (rab)
Inhalative	LC50/4h	17.8 mg/l (rat)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation No sensitising effects known.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 7)

GB

mofakult.ch

mofakult.ch

Version number 9 (replaces version 8) Printing date 22.11.2021 Revision: 22.04.2021

Trade name: Presto Spachtel styrolfrei alle Qualitäten

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

ult.ch

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA

- · 14.2 UN proper shipping name
- $\cdot ADR$

· IMDG, IATA

3269 POLYESTER RESIN KIT POLYESTER RESIN KIT

- · 14.3 Transport hazard class(es)
- mofakult ch· ADR



· Class

3 (F3) Flammable liquids.

- ·Label

· IMDG, IATA



~1
lace

mofakult ch

3 Flammable liquids.

 \cdot Label

- · 14.4 Packing group
- · ADR, IMDG, IATA

III

· 14.5 Environmental hazards:

Not applicable.

- · 14.6 Special precautions for user · Hazard identification number (Kemler code):
- Warning: Flammable liquids.

· EMS Number:

F-E,S-D

· Stowage Category

- · 14.7 Maritime transport in bulk according to IMO

instruments

Not applicable.

(Contd. on page 8)

(Contd. of page 6) falult.ch

mofakult.ch

mofakult.ch

mofakult.ch

mofakult

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2021 Version number 9 (replaces version 8) Revision: 22.04.2021

Trade name: Presto Spachtel styrolfrei alle Qualitäten

		mofakult.ch	Contd. of page 7) facult.	
· Transport/Additional informat	ion:			
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code		5L Code: E0 Not permitted as Excepted Quantity kult ch 3 E	Þ	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)		5L Code: See SP340		
· UN "Model Regulation":	S	UN 3269 POLYESTER RESIN KIT, 3, III	mofakult.	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

motal H319 Causes serious eye irritation. of akultuda

H332 Harmful if inhaled.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)

GB

mofakult.ch

mofakult.ch

Safety data sheet according to 1907/2006/EC, Article 31

mofakult,cl

Printing date 22.11.2021

Version number 9 (replaces version 8)

Revision: 22.04.2021



(Contd. of page 8) ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern mofakult.ch vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2 mofakult.ch Carc. 2: Carcinogenicity – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 * Data compared to the previous version altered.

mofakult.ch	Ø	mofakult.ch	Ø	mofakult.ch	GB —

motakult.ch motakult.ch motakult.ch motakult.ch



Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2021 Version number 15 (replaces version 14) Revision: 21.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Hardener Paste
- · Article number:

80692, 80694, 80695, 80702, 80703, 80704, 80705, 80706, 80707, 80711, 80716, 80719, 80726, 80753, 81255, 81275, 81276, 85302, 360268, 499191, 499603, 600078, 600160, 600177, 600269, 600276, 784866, 80267alt, 80400alt, 80691alt, 80693alt, 80696alt, 80697alt, 80698alt, 80700alt, 80701alt, 80708alt, 80710alt, 80712alt, 80728alt, 80754alt

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9b Fillers, putties, plasters, modelling clay
- · Process category PROC10 Roller application or brushing
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

- *Formerly known as Motip Dupli GmbH
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

mofakult,ch

mofakult.ch

mofakult.ch

Public emergeny phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland.

Poison center if childs have been poisened: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Org. Perox. E

H242 Heating may cause a fire.

(Contd. on page 2)

GB

mofakult.ch

mofakult.ch

Printing date 22.11.2021 Version number 15 (replaces version 14) Revision: 21.09.2021

Trade name: Hardener Paste

akult.ch (Contd. of page 1) akult.ch



Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



mofakult.cl

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Warning

 $\cdot \textit{Hazard-determining components of labelling:}$

dibenzoyl peroxide

· Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

mofal Litt.ch H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if mofacult.ch

present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents / container in accordance with regional regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 94-36-0 EINECS: 202-327-6

EINECS: 202-327-6

Index number: 617-008-00-0 Reg.nr.: 01-2119511472-50

dibenzoyl peroxide

🤣 🅸 Org. Perox. B, H241

Aquatic Acuté 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10)

Eye Irrit. 2, H319; Skin Sens. 1, H317

(Contd. on page 3)

25-<50%

GB -

mofakult.ch

mofakult.ch

mofakult.ch

Urheber des Dokuments bleibt der ursprüngliche Herau

mofakult

mofakult

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2021 Version number 15 (replaces version 14) Revision: 21.09.2021

Trade name: Hardener Paste

mofakult . ch	mofakult.ch	(Contd. of page 2)
CAS: 131-11-3 EINECS: 205-011-6 Reg.nr.: 01-2119437229-36	dimethyl phthalate substance with a Community workplace exposure limit	25-<50%
CAS: 107-21-1 EINECS: 203-473-3 Index number: 603-027-00-1	ethanediol	5-<10%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Seek immediate medical advice.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

No further relevant information available.

- · 5.3 Advice for firefighters -
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling No special measures required.

(Contd. on page 4)

GB

mofakult.ch

Printing date 22.11.2021 Version number 15 (replaces version 14) Revision: 21.09.2021

Trade name: Hardener Paste

(Contd. of page 3) falult.ch

- · Information about fire and explosion protection: Keep ignition sources away Do not smoke.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 5.2
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection kult.ch

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

131-11-3 dimethyl phthalate

WEL Short-term value: 10 mg/m³

Long-term value: 5 mg/m³ mofakult.ch

107-21-1 ethanediol

WEL Short-term value: 104** mg/m³, 40** ppm

Long-term value: 10* 52** mg/m³, 20** ppm

Sk *particulate **vapour

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection



mofakult,ch

Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min kylene

Xylene: 42 min kull.ch
Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective
measure, we recommend that users and responsible persons for work safety assume solvent resistance length
of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in
particular cases.

(Contd. on page 5)

GB

mofakult.ch

Version number 15 (replaces version 14) Printing date 22.11.2021 Revision: 21.09.2021

Trade name: Hardener Paste

· Eye/face protection

(Contd. of page 4) falult.ch

mofakult.ch

mofakult.ch

mofakult.ch

mofakult.ch



*

mofakult ch

mofakult

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid mofakult.ch · Colour: Pink

· Odour: Characteristic· Odour threshold: Not determined. · Melting point/freezing point:

· Boiling point or initial boiling point and boiling

range

· Flammability · Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable. · Decomposition temperature: *50 °C (122 °F) (SADT)*

· pH at 20 °C (68 °F)

· Viscosity:

· Kinematic viscosity · Dynamic:

· Solubility · water:

· Partition coefficient n-octanol/water (log value)

· Vapour pressure at 20 $^{\circ}C$ (68 $^{\circ}F$):

· Density and/or relative density · Density at 20 °C (68 °F):

· Relative density · Vapour density Undetermined.

100 °C (212 °F) (7732-18-5 water, distilled,

Not applicable.

conductivity or of similar purity)

Not determined. Not determined.

Not miscible or difficult to mix.

Not determined.

23 hPa (17.3 mm Hg) (7732-18-5 water, distilled,

conductivity or of similar purity)

 $1.1 \text{ g/cm}^3 (9.2 \text{ lbs/gal})$

Not determined. Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health and environment, and on safety.

ult ch. Ignition temperature: 410 °C (770 °F)

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· Organic solvents: 9.0 % · Water: 11.0 % · **VOC** (**EC**) -- %

112.6 g/l · VOC-EU% 9.00 % · Solids content: 55.0 %

· Change in condition

· Evaporation rate Not determined.

mofakult.c (Contd. on page 6)

Printing date 22.11.2021 Version number 15 (replaces version 14) Revision: 21.09.2021

Trade name: Hardener Paste

(Contd. of page 5)

ofakult.ch

mofakult.ch

mofakult.ch

mofakult.ch

-		
· Information with regard to physical hazard classe	S	
· Explosives	Void	
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
Ch. Gases under pressure mofakult.ch	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void mofakult.ch	
Substances and mixtures, which emit flammable		
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Heating may cause a fire.	
. Corrosive to metals	Void	
Desensitised explosives	Void	
	Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures Substances and mixtures Oxidising solids Oxidising solids Organic peroxides Corrosive to metals	Flammable gases Aerosols Oxidising gases Flammable liquids Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures Substances and mixtures Substances and mixtures Void Void Void Oxidising liquids Oxidising solids Organic peroxides Corrosive to metals

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- mofal ult.ch. 12.7 Other adverse effects
 - · Remark: Very toxic for fish

(Contd. on page 7)

GB

mofakult.ch

Safety data sheet according to 1907/2006/EC, Article 31

Version number 15 (replaces version 14) Printing date 22.11.2021 Revision: 21.09.2021

Trade name: Hardener Paste

(Contd. of page 6) falult.ch

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECTION	14:	Trans	port in	forma	tion

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN3108
- · 14.2 UN proper shipping name
- 3108 ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl $\cdot ADR$
 - peroxide), ENVIRONMENTALLY HAZARDOUS
- · IMDG, IATA ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl
 - peroxide)

Warning: Organic peroxides.

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



- · Class 5.2 (P1) Organic peroxides.
- · Label
- · IMDG, IATA



mofakult ch

mofakult

- · Class 5.2 Organic peroxides.
- · Label 5.2
- · 14.4 Packing group
- · ADR, IMDG, IATA not regulated
- · 14.5 Environmental hazards:
- · Marine pollutant:
- · Special marking (ADR): Symbol (fish and tree)
- · 14.6 Special precautions for user
- · Hazard identification number (Kemler code):
- · EMS Number:
- F-J,S-R· Stowage Category D

(Contd. on page 8)

ofakult.ch

mofakult.ch

mofakul

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2021 Version number 15 (replaces version 14) Revision: 21.09.2021

Trade name: Hardener Paste

mofakult.ch	\$	mofakult.ch	(Contd. of page 7)
· Stowage Code · Segregation Code		SW1 Protected from sources of heat. SG35 Stow "separated from" SGG1-acia SG36 Stow "separated from" SGG18-alk SG72 See 7.2.6.3.2.	
14.7 Maritime transport in bull instruments	k according to IM	O mofakult Not applicable.	.ch
· Transport/Additional informat	ion:		
 ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code 		500 g Code: E0 Not permitted as Excepted Quantity 2 D	mofakult.ch
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	mofakult.ch	500 g Code: E0 Not permitted as Excepted Quantity	.ch 👂
· UN ''Model Regulation'':		UN 3108 ORGANIC PEROXIDE TYPE I (DIBENZOYL PEROXIDE), 5.2, ENVIR HAZARDOUS	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- mofakult.ch. Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H241 Heating may cause a fire or explosion.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

mofal ult. RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

(Contd. on page 9)

GB

akult.ch

mofakult.ch

Page 9/9

mofakult.ch

mofakult.ch

Safety data sheet according to 1907/2006/EC, Article 31

mofakult.ch

Printing date 22.11.2021

Version number 15 (replaces version 14)

Revision: 21.09.2021

(Contd. of page 8) falult.ch

mofakult.ch

GB

Trade name: Hardener Paste

motakult₌cn

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Org. Persy, B: Organic persyides - Type B

Org. Perox. B: Organic peroxides – Type B Org. Perox. E: Organic peroxides – Type E/F

Acute Tox. 4: Acute toxicity – Category 4
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* * Data compared to the previous version altered.

molakuluch molakuluch molakuluch

mofakult.ch mofakult.ch mofakult.ch mofakult.ch

mofakult.ch mofakult.ch mofakult.ch

mofakult.ch mofakult.ch mofakult.ch mofakult.ch

mofakult.ch mofakult.ch mofakult.ch

mofakult.ch mofakult.ch mofakult.ch mofakult.ch

mofakult.ch mofakult.ch mofakult.ch mofakult.ch

nofakult.ch mofakult.ch